

VENEZIA

**Douchescharnieren en
klemmen**

Shower hinges and clamps



**DOUCHE
CABINE
ACCESSOIRES**

**SHOWER
BOXES
ACCESSORIES**

GLAS TECH
Solutions bv

ACCESSOIRES VOOR HARDGLAS



INTELBAARE SCHARNIEREN TGAH 800 SERIES

ADJUSTABLE HINGES TGAH 800 SERIES



TGAH801OS

Instelbaar scharnier enkelzijdige bevestiging (glas - wand)

Adjustable hinge, offset fixing plate (glass to wall)



TGAH801

Instelbaar scharnier (glas - wand)

Adjustable hinge (glass to wall)



TGAH802

Instelbaar scharnier 180° (glas - glas)

Adjustable hinge 180° (glass to glass)




TGAH804

Instelbaar scharnier 90° (glas - glas)

Adjustable hinge 90° (glass to glass)


Instel instructies voor 0 punt instelling TGAH series

1. Gebruik imbussleutel (A) draai imbusschroef (B) los
2. Open afdekkapje (C)
3. Gebruik imbussleutel (D) draai schroeven (E) 1 slag los begin met 0 punt instelling
4. Na instelling 0 punt (max $\pm 10^\circ$) draai de 4 schroeven (E) stevig vast
5. Monteer afdekkapje
6. Draai schroef (B) vast
7. **NOTE:** Controleer of schroeven E goed vast gedaan zijn ook al is er geen 0 punt instelling gemaakt



Angle adjustment instruction TGAH series

1. Use hexagon key (A) to unfasten the screw (B)
2. Open the cover (C)
3. Use hexagon key (D) to unfasten 4 screw (E) by turning 1 circle possibly then proceed with the adjustment
4. After done with the angle adjustment (max $\pm 10^\circ$), fasten 4 screws (E) tightly
5. Close the cover
6. Fasten screw (B)
7. **NOTE:** Check tightness of screws E, even if angle adjustment was not made



TGAH801OS


Instelbaar scharnier enkelzijdige bevestiging (glas - wand)
 Adjustable hinge, offset fixing plate (glass to wall)



Code	Finish / Finish
TGAH801OS PC	chrom gepolijst / polish chrome
TGAH801OS SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 6; 8	glass thickness (mm): 6; 8
max. deurgewicht per paar (kg): 45	max. door weight per pair (kg): 45
max. deurbreedte (mm): 750	max. door width (mm): 750

GLAS TECH
Solutions b.v.

Quality product of **P.M.**




TGAH801

Instelbaar scharnier (glas - wand)
 Adjustable hinge (glass to wall)




Code	Finish / Finish
TGAH801 PC	chrom gepolijst / polish chrome
TGAH801 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 6; 8	glass thickness (mm): 6; 8
max. deurgewicht per paar (kg): 45	max. door weight per pair (kg): 45
max. deurbreedte (mm): 750	max. door width (mm): 750






TGAH802

Instelbaar scharnier (glas - glas 180°)
Adjustable hinge (glass to glass 180°)



Glasbewerking
Glass preparation



Glasbewerking
Glass preparation


Code

TGAH802 PC

TGAH802 SC

materiaal: messing

glasdikte (mm): 6; 8

max. deurgewicht per paar (kg): 45

max. deurbreedte (mm): 750

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

material: brass

glass thickness (mm): 6; 8

max. door weight per pair (kg): 45

max. door width (mm): 750

TGAH804

Instelbaar scharnier (glas - glas 90°)
Adjustable hinge (glass to glass 90°)


Code

TGAH804 PC

TGAH804 SC

materiaal: messing

glasdikte (mm): 6; 8

max. deurgewicht per paar (kg): 45

max. deurbreedte (mm): 750

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

material: brass

glass thickness (mm): 6; 8

max. door weight per pair (kg): 45

max. door width (mm): 750

INSTELBARE VERTICAAL SCHARNIEREN TGAH 500 SERIES **ADJUSTABLE VERTICALLY PIVOTED HINGES TGAH 500 SERIES**



TGAH501LOS

Instelbaar verticaal draaiend
 scharnier wandmontage
 links

Adjustable vertically pivoted hinge
 wall installation, left



TGAH501ROS

Instelbaar verticaal draaiend
 scharnier wandmontage
 rechts

Adjustable vertically pivoted hinge
 wall installation, right



TGAH505

Instelbaar verticaal draaiend
 scharnier vloer / plafond
 montage



Adjustable vertically pivoted hinge,
 floor / ceiling installation

Instel instructies voor 0 punt instelling TGAH series

1. Gebruik imbussleutel (**D**) draai schroeven (**A B**) 1 slag los begin met 0 punt instelling
2. Na instelling 0 punt (max $\pm 30^\circ$) draai de 4 schroeven (**A B**) stevig vast
3. NOTE: Controleer of schroeven A & B goed vast gedraaid zijn ook al is er geen 0 punt instelling gemaakt


Angle adjustment instruction

1. Use hexagon key (**D**) to unfasten screw (**A B**) by turning 1 circle possibly then proceed with the adjustment
3. 4. After done with the angle adjustment (max $\pm 30^\circ$), fasten screws (**A B**) tightly
3. **NOTE:** Check tightness of screws **A B**, even if angle adjustment was not made






TGAH501LOS

Instelbaar verticaal scharnier wandmontage, links
 Adjustable vertically pivoted hinge wall installation, left



Glasbewerking
 Glass preparation


Code

TGAH501LOS PC

TGAH501LOS SC

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

materiaal: messing

glasdikte (mm): 8;10

max. deurgewicht per paar (kg): 55

max. deurbreedte (mm): 800

material: brass



glass thickness (mm): 8; 10

max. door weight per pair (kg): 55



max. door width (mm): 800

TGAH501ROS

Instelbaar verticaal scharnier wandmontage, rechts
 Adjustable vertically pivoted hinge wall installation, right



Glasbewerking
 Glass preparation


Code

TGAH501ROS PC

TGAH501ROS SC

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

materiaal: messing

glasdikte (mm): 8; 10

max. deurgewicht per paar (kg): 55

max. deurbreedte (mm): 800

material: brass

glass thickness (mm): 8; 10

max. door weight per pair (kg): 55






max. door width (mm): 800

TGAH505

Instelbaar verticaal scharnier, vloer / plafond montage
 Adjustable vertically pivoted hinge,
 floor / ceiling instalation

GLAS TECH
Solutions b.v.

Quality product of **P&M**



Glasbewerking
 Glass preparation

Code	Finish / Finish
TGAH505 PC	chrom gepolijst / polish chrome
TGAH505 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10	glass thickness (mm): 8; 10
max. deurgewicht per paar (kg): 55	max. door weight per pair (kg): 55
max. deurbreedte (mm): 800	max. door width (mm): 800

GLAS TECH
Solutions b.v.

STANDAARD SCHARNIEREN TGSH 500 SERIES STANDARD HINGES TGSH 500 SERIES



TGSH505LOS
Standaard verticaal scharnier
wandmontage, links

Standard vertically pivoted
hinge, wall installation, left




TGSH505ROS
Standaard verticaal scharnier
wandmontage, rechts

Standard vertically pivoted hinge,
wall installation, right



TGSH505
Standaard verticaal scharnier
vloer / plafondmontage

Standard vertical pivoted hinge,
floor / ceiling installation



TGSH505LOS

Standaard verticaal scharnier wandmontage, links
Standard vertically pivoted hinge wall installation, left



Code	Finish / Finish
TGSH505LOS PC	chromo gepolijst / polish chrome
TGSH505LOS SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10	glass thickness (mm): 8; 10
max. deurgewicht per paar (kg): 55	max. door weight per pair (kg): 55
max. deurbreedte (mm): 800	max. door width (mm): 800

GLAS TECH
Solutions b.v.

STANDAARD KLEMMEN TGSC SERIES STANDARD CLAMPS TGSC SERIES



TGAC701

Instelbare klem (glas - wand), H=51 mm
Adjustable clamp (glass to wall), H=51 mm




TGAC704


Instelbare klem (glas - wand), H=51 mm
Adjustable clamp (glass to glass), H=51 mm

TGAC701


Instelbare klem (glas - wand), H=51mm
Adjustable clamp (glass to wall), H=51mm



Glaskant 45°
Glass edge 45°



Glasbewerking
voor 45°
Glass preparation for 45°



Glasbewerking
voor 90°
Glass preparation for 90°

Code

TGAC701 PC

TGAC701 SC

materiaal: messing

glasdikte (mm): 8; 10; 12

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

material: brass




glass thickness (mm): 8; 10; 12

TGAC704



Instelbare klem (glas - glas), H=51
Adjustable clamp (glass to glass), H=51

GLAS TECH
Solutions bv.

Quality product of **P.M.**



Glasbewerking voor 180 °
Glass preparation for 180 °



Glasrand 22.5 °
Glass edge 22.5 °

Glasbewerking voor 135 °
Glass preparation for 135 °

Code	Finish / Finish
TGAC704 PC	chrom gepolijst / polish chrome
TGAC704 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12

STANDAARD KLEMMEN TGSC SERIES STANDARD CLAMPS TGSC SERIES



TGSC701

Standaard klem
(glas - wand), H=51mm

Standard clamp
(glass to wall), H=51 mm



TGSC702

Standaard klem 180°
(glass - glass), H=51mm

Standard clamp 180°
(glass to glass), H=51 mm



TGSC704

Standaard klem 90°
(glass - glass), H=51mm

Standard clamp 90°
(glass to glass), H=51 mm



TGSC501

Standaard klem
(glas - wand), H=72mm

Standard clamp
(glass to wall), H=72 mm



TGSC502

Standaard klem 180°
(glass - glass), H=72mm

Standard clamp 180°
(glass to glass), H=72 mm



TGSC504

Standaard klem 90°
(glass - glass), H=72mm

Standard clamp 90°
(glass to glass), H=72 mm

TGSC701




Klem (glas - wand), H=51
 Clamp (glass to wall), H=51



Code	Finish / Finish
TGSC701 PC	chrom gepolijst / polish chrome
TGSC701 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte: 8; 10; 12	glass thickness: 8; 10; 12

GLAS TECH
Solutions b.v.

Quality product of **P.M.**



Glasbewerking: speling 5 mm
 Glass preparation: gap 5 mm



Glasbewerking: stelbaar 0-5 mm
 Glass preparation: adjustments 0-5 mm

TGSC702

Klem (glas - glas) 180°
 Clamp (glass to glass) 180°




Code	Finish / Finish
TGSC702 PC	chrom gepolijst / polish chrome
TGSC702 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12



Glasbewerking
 Glass preparation

GLAS TECH
Solutions b.v.
TGAC704

Klem (glas - glas), 90° H=51mm
Clamp (glass to glass), 90° H=51mm



Glasbewerking
Glass preparation

GT- Glasdikte
Glass thickness







Code	Finish / Finish
TGAC704 PC	chrom gepolijst / polish chrome
TGAC704 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12

TGSC501


Klem (glas - wand), H=72
Clamp (glass to wall), H=72

GLAS TECH
Solutions b.v.

Quality product of **P.M.**



Glasbewerking: speling 5 mm
Glass preparation: gap 5 mm





Glasbewerking: stelbaar 5 mm
Glass preparation: adjustments 0-5 mm

Code	Finish / Finish
TGSC501 PC	chrom gepolijst / polish chrome
TGSC501 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12

GLAS TECH
Solutions b.v.

TGSC502

Klem (glas - glas), 180° H=72 mm
Clamp (glass to glass), 180° H=72 mm



Glasbewerking
Glass preparation




Code	Finish / Finish
TGSC502 PC	chrom gepolijst / polish chrome
TGSC502 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12

TGSC504

Klem (glas - wand), 90° H=72
 Clamp (glass to wall), 90° H=72

GLAS TECH
Solutions b.v.

Quality product of **P.M.**







Glasbewerking
 Glass preparation

Code	Finish / Finish
TGSC504 PC	chrom gepolijst / polish chrome
TGSC504 SC	look rvs / satin chrome
materiaal: messing	material: brass
glasdikte (mm): 8; 10; 12	glass thickness (mm): 8; 10; 12

TGLI70H

Slot met rood / groen indicatie en greep
 Indication lock with lever handle

Glasbewerking
 Glass preparation


Code

TGLI70H PC

TGLI70H SC

materiaal: messing

glasdikte (mm): 8; 10; 12

inclusief sluitplaat

Finish / Finish

chrom gepolijst / polish chrome




look rvs / satin chrome

material: brass

glass thickness (mm): 8; 10; 12

keeper plate included

Glasbewerking
 Glass preparation


TGSI70H

Tegenkast
 Strike box


Code

TGSI70H PC

TGSI70H SC

materiaal: messing

glasdikte (mm): 8; 10; 12

voor slot: TGLI70H

Finish / Finish

chrom gepolijst / polish chrome

look rvs / satin chrome

material: brass

glass thickness (mm): 8; 10; 12

for lock: TGLI70H

TGL10S

Loopslot met rood - groen indicator
 Washroom indicator lock



Code	Finish / Finish
TGLI10S SSS	rvs geborsteld / satin stainless steel
TGLI10S PSS	rvs gepolijst / polished stainless steel
glasdikte (mm): 8; 10; 12	
Exclusief deurklink en sluitplaat	
glass thickness: 8; 10; 12	
Lever handle, keeper and keeper plate not included	

TGS10S






Tegenkast
 Strike patch



Code	Finish / Finish
TGS10S SSS	rvs geborsteld / satin stainless steel
TGS10S PSS	rvs gepolijst / polished stainless steel
glasdikte (mm): 8; 10; 12	
For locks: TGL35S, TGL35SNH, TGLI30S	
glass thickness: 8; 10; 12	
For locks: TGL35S, TGL35SNH, TGLI30S	

GLAS TECH
Solutions b.v.




Glasbewerking
 Glass preparation



TGLI30S slot kan voor zowel binnen draaiende als naar buitendraaiende deuren gebruikt worden d.m.v. daaiknop van zijde te verwisselen






TGLI30S indicator lock can be used for both outwarddoor and inward door by exchanging the thumbturn side

Glasbewerking
 Glass preparation



Loopslot met rood - groen indicator
Washroom indicator lock

Glasbewerking
Glass preparation



TGLI30S slot kan voor zowel binnen draaiende als naar buitendraaiende deuren gebruikt worden d.m.v. daaiknop van zijde te verwisselen

TGLI30S indicator lock can be used for both outwarddoor and inward door by exchanging the thumbturn side







Code	Finish / Finish
TGLI30S SSS	rvs geborsteld / satin stainless steel
TGLI30S PSS	rvs gepolijst / polished stainless steel
glasdikte (mm): 8; 10; 12	glass thickness: 8; 10; 12
Exclusief deurklink en sluitplaat	Lever handle, keeper and keeper plate not included

TGS30S

Tegenkast
Strike patch

Glasbewerking
Glass preparation



Code	Finish / Finish
TGS30S SSS	rvs geborsteld / satin stainless steel
TGS30S PSS	rvs gepolijst / polished stainless steel
glasdikte (mm): 8; 10; 12	glass thickness: 8; 10; 12
For locks: TGL35S, TGL35SNH, TGLI30S	For locks: TGL35S, TGL35SNH, TGLI30S



www.glastech.eu



GLASS HARDWARE Be Ne De Lux

Burgemeester van Meeuwenstraat 2
6191 ND Beek (LB)
The Netherlands

Tel: +31(0) 46 428 07 28
sales@glastech.eu

www.glastech.eu